

# 6X6 AIRPORT RESCUE & FIREFIGHTING VEHICLE



### Specifications - Meets ICAO Standards

Chassis		Control System		
Туре	Custom 6x6 ARFF	Туре	Marcé electronic pump control system	
Engine Output	Rear Mounted - 605Hp, (447kW) Euro 3			
Transmission	Automatic Transmission	Fire fighting system		
Wheels	Michelin 525/65R20.5 single tyres	Centrifugal pump 6500 l/min @ 10 bar NP and 250 l/min @ 40 bar HP		
Acceleration	0-80.5 km/h < 35 seconds			
Top Speed	> 115 km/h		ATP pump foam system	
Static Tilt	28°	Water tank	Water tank : 9000 litre	
Suspension	Coil spring with double acting hydraulic shock absorbers	Foam tank : 1100 litre		
		Mamba 3 Roof and Bumper Turret (3000 I/min)		
Brakes	Ventilated disc brakes with ABS and EBD	DCP: 250 k	٨ġ	
Driving and crew compartment		Pump discharges		
Cab	Marcé panoramic aluminium cab - certified ECE R 29 -3 (Seating 1+3)	4 x Handlin deluge syst	ies, 2 x hose reels, under truck nozzles and cab tem	

Vehicle body

Aluminium and GRP with two lockers on each side



## 6X6 AIRPORT RESCUE & FIREFIGHTING VEHICLE

#### Lighting

Two LED scene lights at rear of body
--------------------------------------

Two LED scene lights each side of the vehicle

LED ground lights under vehicle

LED Pneumatic Light Mast

Two LED locker lights in each locker

Emergency lighting and siren system

Two Red LED light bar

Two blue water level indicators / Two yellow foam Indicators

Red LED flashers on vehicle

100w Public address and siren system

Ancillary equipment and fixtures

ICAO fire fighting equipment

Reverse camera with screen on dashboard

### Vehicle dimensions

Wheelbase	5550 mm
Length	11289 mm
Height	3759 mm
Width	2595 mm excl mirrors







