





Specifications

Chassis		Fire fighting system
Туре	Mercedes-Benz Unimog U5000 4x4 SC	PTO driven pump - pump and drive capable
Engine Output	160kW @ 2200rpm	Automatic ATP Foam System
Transmission	Automatic	3000 l/min @ 10 bar
Driving and crew compartment		400 l/min # 40 bar
		Marcé Mamba 3 Monitor 3000 l/min - Joystick controlled
Cab	Driver plus one	Water Tank : 4000 litre
Vehicle features		Foam Tank : 200 litre
Jump Seats	Two at rear with 3 point safety belts	Marcé Pump Control Unit with LED tank gauge, foam induc- tion selector and analog guage indicators
Lighting	LED lightmast	tion selector and analog guage indicators
Protection	Ground sweeps and cab deluge system	Hose reels
Bull Bar	Heavy duty bull bar with winch	Two 30m x 25mm hose reels c/w nozzles fitted on the rear.
		one each side of the pump
Vehicle body		
Marcé all aluminium extrusion and bended plate body welded		Pump discharges
for added strength and durability		Four (4) x 65mm discharges with BIC couplings
Two body compartments with Roller shutter doors		



PUMPERS 4x4 Unimog Bush Pumper

Emergency lighting and siren system

Red LED light bar

Red LED flashers on vehicle

100w Public address and siren system

Ancillary equipment and fixtures

Hydraulic Rescue Equipment - Battery Operated

Firefighting Equipment

LED illumination for lockers





